

Dual Clam Shell With Articulating Arm and Small Plate

Item #7160-0420



Placement

Attaches to rectangular forklift support braces 1.5" to 2.5" wide

Tilt

Yes - Clevis up to 90° fore

Yes - Clam Shells up to 160°

Swivel

Motion Attachment - 360°

Entire arm - 360°

Weight

7.95 lbs. / 3.6 kg

Dimensions

Height: 10.08" / 25.6 cm

Width: 7.43" / 18.9 cm

Depth: 9.96" / 25.3 cm

Clam Shell Features

- Heavy gauge steel construction for long-term durability in a rugged environment
- Black powdercoat finish for maximum corrosion resistance
- Clam Shell features the following hole patterns: AMPS, NEC, 75mm VESA, Gamber-Johnson 2"x 4.09"
- The entire arm can rotate around 360° and the Motion Attachment can also rotate 360°
- Arm extends, bringing equipment closer to the user
- Arm can be tighten down to be locked into a permanent position
- Tilt capabilities:
 - 90° forward allows for tablets to be easily mounted
 - 26° aft movement with a positive stop at 26°
 - Riveted design allows for smoother tilt movement
- To tilt the Clam Shell simply loosen the adjustable lever, tilt to desired position and then re-tighten the lever
- A secondary bolt is included to lock the clevis into a permanent position
- Limited Lifetime Warranty

Small Plate Features

- Heavy gauge steel construction for long-term durability in a rugged environment
- Black powdercoat finish for maximum corrosion resistance
- Clam Shell features the following hole patterns: AMPS, NEC and 75mm VESA
- The Clam Shell can be tilted up or down for a total of 160°
- To tilt the Clam Shell simply loosen the adjustable lever, tilt to desired position and then re-tighten the lever
- A secondary bolt is included to lock the clam shell into a permanent position
- Plate sandwiches the overhead guard leg and allows user to position the device at the desired height position
- Limited Lifetime Warranty