



Very Well Connected™

INSTALLATION INSTRUCTIONS

Product

7160-0756

FLEX MOUNT W/ VESA 75 PLATE

Revision

Rev.A

Form

INST-678

Printing Spec: PS-001

ASSEMBLY:

1. Loosely install the two u-bolts to the foot using the supplied hardware.
2. Remove loom from aluminum rod.
3. Install the foot assembly onto the end of the aluminum rod and loosely tighten u-bolts.
4. Bolt foot to desired mounting point in vehicle (hardware not included). The most convenient mounting point in most vehicles is the front left passenger seat mounting bolt (bolt foot between seat rail and floor of vehicle). If your vehicle does not have front seat mounting bolts (most GM cars), you will need to find another suitable mounting point.
5. The aluminum bar can be bent or cut to length to customize installation. The bar can be bent in a vice, or over the edge of a board or workbench.
6. Once final shape is attained, reinstall loom, place rod in u-bolts and tighten.
7. Install the mounting plate to the tube with the supplied bolt and lock washer and install the equipment that needs to be attached to the plate using the hardware that was provided with the equipment (display unit etc)
8. For additional stability the assembly can be secured to a vertical surface such as the side of the center console using the supplied plastic mount. Attach the plastic mount to a suitable surface and the aluminum rod with the included cable tie. Before driving any screws into your car check for the presence of vehicle systems. Gamber-Johnson recommends that any modifications to your vehicle be completed by an experienced installer.



Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2014 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868



Very Well Connected™



- You must read and follow all of these installation instructions. Failure to follow all of these installation instructions may result in serious bodily injury or death.
- Keep these installation instructions with the product and readily available in the vehicle for future reference of other users of the product.
- Additional copies of the installation instructions can be obtained from Gamber Johnson.
- If you need assistance or have any questions, call Gamber-Johnson at 1-800-456-6868.
- Do not remove warning label from product under any circumstances.
- Before installation of any equipment always check area for routing of wires / cables and if drilling is required check area where drilling above and below the drilling area.
- High speed vehicle turns may cause a motion attachment product to swivel, interfering with the driver or other equipment.
- The Vehicle Base, Upper Pole, Motion Attachment and Dock or Cradle should not be positioned in the area where the airbag will be deployed if it is activated. **DO NOT** position the equipment in front of an airbag. Equipment positioned in front of an airbag can cause serious injury or death if an airbag was activated, such as in an accident.
- The installer and user of this product(s) are responsible for installing and using Upper Pole, Motion Attachment and Dock or Cradle assemblies outside the airbag deployment zone. (See Product Mounting Disclaimer Below)
- If installation of the equipment requires that the equipment be placed in front of an airbag, deactivate the airbag in the vehicle so it cannot be activated in an accident. In order to secure permission for deactivating the airbag in these circumstances, contact the National Highway Traffic Safety Administration at 1-800-424-9393 to gain permission to do so. If you have any questions or need assistance, call Gamber Johnson at 1-800-456-6868.

Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2014 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868