

Testing Summary

Panasonic Toughbook L1 Tablet Docking Station

(7160-1314-00, 7160-1314-02, 7160-1314-10, 7160-1314-12) Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration –	Panasonic's Toughbook criteria per graph B, tailored MIL-STD 810G
Operational	514.6. Test duration is 2 hours along three mutually orthogonal
Test date: July, 2019	axes – not simultaneously (6 hours total).
	Unit is unlocked
Vibration –	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure
Operational	514.6C-1. Test duration is 2 hours along three mutually orthogonal
RF Connection	axes – not simultaneously (6 hours total).
Test date: July, 2019	Unit is unlocked
	Panasonic provided operating conditions
	Test is performed simultaneously with operational test.
	Test is monitored to record any breaks in RF connectivity
	during vibration.
Vibration –	Panasonic's Toughbook tested criteria per graph A.MIL-STD-810G,
Non-Operational	Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one
(Minimum Integrity)	hour along three mutually orthogonal axes – not simultaneously (3
Test date: August, 2019	hours total).
	Unit is unlocked
	Tested in both laptop and tablet orientations.
Functional Shock -	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative
Non-Operational	pulses each axis (vertical, longitudinal and transverse), 18 pulses
Test date: July 2019	20G, 11ms half sine
	Unit is unlocked
Mechanical Shock	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative
Safety -	pulses each axis (vertical, longitudinal and transverse), 18 pulses
Non-Operational	40G, 11ms half sine
Test date: July, 2019	Unit is unlocked
Cycle Testing –	30,000 cycles of the docking connector, latching and locking
Non-Operational	mechanisms
Test date: October, 2019	THE CHAINSTITS
130 0000 000001, 2015	

An ISO 9001:2015 certified company



Electrostatic	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
Discharge –	
Operational	
Test date: June, 2019	

Summary of Tests Performed at Independent Facility

Test Description	Test Parameters	
Humidity	MIL-STD 810G, Method 507.5, Procedure II, Aggravated	
Test date: June, 2019	 Ten 24-hour cycles, temperature varied from 30°C to 60°C 	
	to 30°C at constant 95% relative humidity.	
	,	
Thermal Shock	Panasonic Toughbook Criteria Specification	
Test date: June, 2019	85°C to -40°C, Non-Operating	
	2hrs at each temperature, 50 cycles	
Low Temperature:	MIL-STD 810G, Method 502.5, Procedure I	
Operational Test date: June, 2019	 -20°C Operating, 24 hours 	
Low Temperature:	MIL-STD 810G, Method 501.5, Procedure II	
Storage	 -40°C Operating, 24 hours 	
Test date: June, 2019		
Cold Resistance:	Panasonic Toughbook Criteria Specification	
Test date: June, 2019	 -40°C Non-Operating, 72 hours 	
High Temperature:	MIL-STD 810G, Method 501.5, Procedure II	
Operational	60°C Operating	
Test date: June, 2019	• (5) 24-hour cycles	
High Temperature:	Panasonic Toughbook Criteria Specification	
Storage	96 hour soak at 71°C	
Test date: June, 2019		
Heat Resistance	Panasonic Toughbook Criteria Specification	
Test date: June, 2019	• 72 hour soak at 85°C	
Shock – Crash Hazard	SAE J1455, Section 4.11.3.5, per Figure 13	
Test date: July, 2019	Unit is unlocked	

An ISO 9001:2015 certified company



EMC Testing	EN 50498:2010	
Test date: June, 2019		
EMC Testing	EN 55032:2012	
Test date: June, 2019	 VCCI-CISPR 32 – Class A 	
	 FCC Part 15, Subpart B – Class A 	
Safety Testing	62368	
Test date: July, 2019	• IEC 62368	
	• EN62368-1:2014 + A11:2017	
	• CAN/CSA C22.2 No. 62368-1:2014	
	• UL 62368-1:2014	

Other Certifications

Description	
EN 50581:2012 RoHS2 Directive 2011/65/EU	