



# INSTALLATION INSTRUCTIONS

## Product

7160-0095, 7160-0096, 7160-0099, 7160-0100  
**LED ASSEMBLIES**

## Revision

Rev.B

## Form

INST-386

Printing Spec: PS-001

The LED Assembly is powered using the red and brown wires on the bottom of light base.  
The LED Assembly is designed to operate on 12 volts DC.

In a negative ground vehicle:

Connect the RED wire to the positive pole of the vehicle battery or power distribution box. Install the supplied fuse holder and 1 amp fuse on red wire. Connect the brown wire to a suitable chassis GROUND or the NEGATIVE pole of the battery.

Turn on LED by rotating the Activation Switch on base of LED Assembly.  
The LED Assembly has three positions. Off, Red light, and Red/White light.



### Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2013 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868