

# DEFINING RUGGED

EXCEPTIONAL ENGINEERING | ROCK SOLID | EXTENSIVE TESTING

## MNSTAR POWER DISTRIBUTION HARNESSSES: POWER PREP SERIES

Power Prep Harnesses provide Battery Hot, Ignition, Ground and in some configurations Timed fused outputs. These products feature battery direct power and grounds to provide main power distribution for aftermarket equipment installations. Power Prep Harnesses can be broken down into three basic groups:

- **Full Vehicle Power:** The output wires are either long enough to reach throughout the vehicle or are braided to pre-determined breakout locations throughout the vehicle
- **Power To the Center Console:** A main power feed and fuse panel at the battery with outputs circuits that reach to the center console
- **Power In the Center Console:** A main power feed from the battery to a console mounted fuse panel

## TRUCK HARNESS POWER PREP: FULL VEHICLE POWER DISTRIBUTION

Item No.	Description	Placement	Circuits to Console	Weight
7300-0042	Integrator Truck Harness, 11 Circuits to Console with Ignition Relay (TH45-0)	Underhood Fuse Panel, 125A Master Fuse, Master Cutoff switch Power Distribution Center and Wires that extend to the console and 107" further toward rear of vehicle	3 - Hot lines (30A, 20A, 20A) 8 - Ignition lines (10A each)	6.09 lbs.
7300-0043	Integrator Truck Harness, 11 Circuits to Console with DR40-VM Voltage Sensing Timer (TH45-VM)	Underhood Fuse Panel, 125A Master Fuse, Master Cutoff switch Power Distribution Center and Wires that extend to the console and 107" further toward rear of vehicle	3 - Hot lines (30A, 20A, 20A) 4 - Ignition lines (10A each) 4 - Timed Lines (10A each)	6.09 lbs.

### Features:

- Power Prep Series is designed to work with Commercial Trucks, Police Vehicles and SUV's
- Direct plug in of DR series timers eliminate the need for additional timers to be installed
- Flexible lines capable of reaching console and back of a crew cab or a trunk tray
- Color-Coded and Labeled Wiring
- Detailed Color Schematics
- Direct to Battery Grounds
- Fabricated Wire Harness of High Quality TXL Copper Exceeds SAE Standard J-1128
- Heat Rated: Tested for Maximum Loads at -40°F to 221°F
- Fire Retardant Protective Loom
- Circuits for Timed, Hot and Ignition power
- Warranty terms/policy by MNSTAR:
  - No warranty for Fuses and Solenoids
  - 1 year limited warranty for Relays, Timers, Electronic Control Modules and Circuit Boards
  - 3 year limited warranty for Wire Harnesses, Fuse Panels and Power Distribution Centers

Manufactured by:



Very Well Connected™

3001 Borham Ave. | Stevens Point, WI 54481, USA  
Phone: 715.344.3482 | Toll-free: 800.487.9220 | Fax: 715.344.5209  
Email: [gamberj@gamberjohnson.com](mailto:gamberj@gamberjohnson.com) | Website: [www.gamberjohnson.com](http://www.gamberjohnson.com)

Follow us on:



This document, including images, may not be reproduced partly or fully without the expressed written consent of Gamber-Johnson's Marketing Department.  
© Copyright 2015 Gamber-Johnson LLC