



INSTALLATION INSTRUCTIONS

Product

7160-1695

Keyence BT-A700 non-powered cradle

Revision

Rev A


Form

INST-1076


Printing Spec: PS-001

The Keyence BT-A700 non-powered cradle is designed to hold the BT-A700 series handheld computer in the upright position so the screen can be viewed by the vehicle operator while mounted on a forklift.

Front view



Back view



Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brake lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.


© Copyright 2021 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868

Assembling the cradle to a vehicle mount:

Attach the cradle to a Gamber-Johnson vehicle mount with the #10-32 flat washers and lock nuts found in hardware bag 7120-1002.

The cradle can mount to any Gamber-Johnson vehicle mount with an AMP's hole pattern (30mm X 38mm). Below is one option shown with the 7160-1466 (medium dogbone with 4" diamond plate mount) for reference . This would typically be used to mount to the overhead guard leg on a forklift.



Inserting the computer into the cradle:

- 1. Insert the bottom of the computer into the cradle with the screen facing the operator. The handle will hang below the cradle. (See figure 1.)**
- 2. Rotate the top of the handheld computer into the mount and secure with the cradle latch. The cradle latch is attached with a #10-32 machine screw, lock nut and nylon washers. The torque on the screw can be adjusted by the end user to tighten or loosen the friction latch to the specific desired feel. (See figures 2, 3, & 4)**

Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



different view showing mount hanging from the overhead guard vs the previous photos mounted off the overhead guard leg