

Testing Summary

CF54 Docking Station

(7160-0577, 7160-0578)

Summary of Tests Performed at Gamber-Johnson

| Test Description | Test Parameters |
|--|--|
| Vibration – Operational Test date: July, 2015 | MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions |
| Vibration – Operational RF Connection Test date: July, 2015 | MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions • Test is performed simultaneously with operational test. • Test is monitored to record any breaks in RF connectivity during vibration. |
| Vibration – Non-Operational (Minimum Integrity) Test date: July, 2015 | MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously. <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions |
| Vibration – Non-Operational Sinusoidal Test date: July, 2015 | 10-200Hz Sine Sweep <ul style="list-style-type: none"> • Panasonic provided operating conditions |
| Functional Shock - Non-Operational Test date: July, 2015 | MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 20G, 11ms half sine • Unit is unlocked |
| Mechanical Shock Safety - Non-Operational Test date: July, 2015 | MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 40G, 11ms half sine • Unit is unlocked |
| Cycle Testing – Non-Operational Test date: June, 2015 | 10,000 cycles of the docking connector, latching and locking mechanisms |

An ISO 9001:2008 certified company

| | |
|--|--|
| Electrostatic Discharge – Operational Test date: July, 2015 | ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge |
|--|--|

Summary of Tests Performed at Independent Facility

| Test Description | Test Parameters |
|--|--|
| Shock – Crash Hazard Test date: June 2015 | SAE J1455, Section 4.11.3.5, per Figure 13 <ul style="list-style-type: none"> • Unit is unlocked |
| EMC Testing Test date: May 2015 | <ul style="list-style-type: none"> • E-Mark |
| EMC Testing Test date: July 2015 | EN 55022:2010/AC:2010 <ul style="list-style-type: none"> • CISPR 22 – Class A • FCC Part 15, Subpart B – Class A |
| Safety Testing Test date: July 2015 | 60950 <ul style="list-style-type: none"> • IEC 60950-1/A1:2009 • EN60950-1/A12:2011 • CAN/CSA C22.2 No. 60950-1/A1:2011 • UL 60950-1/R:2011-12 |

Other Certifications

| Description |
|--|
| EN 50581:2012 RoHS2 Directive 2011/65/EU |

An ISO 9001:2008 certified company