

Testing Summary Panasonic Toughbook 40 Laptop Docking Station

(7160-1728)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational	Panasonic's Toughbook criteria per graph B, tailored MIL-STD 810G 514.6. Test duration is 2 hours along three mutually orthogonal
Test date: April, 2022	axes – not simultaneously (6 hours total).Unit is unlocked
Vibration – Operational	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is 2 hours along three mutually orthogonal
RF Connection Test date: April, 2022	axes – not simultaneously (6 hours total).
Τεστ αατε. Αριπ, 2022	Unit is unlockedPanasonic provided operating conditions
	 Test is performed simultaneously with operational test. Test is monitored to record any breaks in RF connectivity during vibration.
Vibration – Non-Operational (Minimum Integrity) Test date: April, 2022	Panasonic's Toughbook tested criteria per graph A.MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total).
	 Unit is unlocked Tested in both laptop and tablet orientations.
Functional Shock - Non-Operational Test date: April, 2022	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses • 20G, 11ms half sine • Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: April, 2022	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses • 40G, 11ms half sine • Unit is unlocked
Cycle Testing – Non-Operational Test date: July , 2022	30,000 cycles of the docking connector, latching and locking mechanisms

An ISO 9001:2015 certified company



Electrostatic	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
Discharge –	
Operational	
Test date: May, 2022	

Summary of Tests Performed at Independent Facility

Summary of Tests Performed at Independent Facility		
Test Description	Test Parameters	
Humidity	MIL-STD 810G, Method 507.5, Procedure II, Aggravated	
Test date: June-July, 2022	 Ten 24-hour cycles, temperature varied from 30°C to 60°C 	
	to 30°C at constant 95% relative humidity.	
Thermal Shock	Panasonic Toughbook Criteria Specification	
Test date: October, 2022	85°C to -40°C, Non-Operating	
	2hrs at each temperature, 50 cycles	
	, , ,	
Low Temperature:	MIL-STD 810G, Method 502.5, Procedure II	
Operational	 -20°C Operating, 24 hours 	
Test date: June-July, 2022		
Low Temperature:	MIL-STD 810G, Method 502.5, Procedure I	
Storage	 -40°C Operating, 24 hours 	
Test date: June-July, 2022	Non-Operational	
Cold Resistance:	Panasonic Toughbook Criteria Specification	
Test date: June-July, 2022	 -40°C Non-Operating, 72 hours 	
	Non Operational	
High Temperature:	MIL-STD 810G, Method 501.5, Procedure II – Induced Conditions	
Operational	50°C Operating	
Test date: June-July, 2022	• (5) 24-hour cycles	
High Temperature:	MIL-STD 810G, Method 501.5, Procedure I – Induced Conditions	
Storage	Non-Operational	
Test date: June-July, 2022	33°C to 71°C w/ humidity as low as possible	
	Seven cycles (one cycle is 24 hours)	
	, , ,	
	•	

An ISO 9001:2015 certified company



Heat Resistance Test date: June-July, 2022	Panasonic Toughbook Criteria Specification • 72 hour soak at 85°C
	Non-Operational
Shock – Crash Hazard	SAE J1455, Section 4.11.3.5, per Figure 13
Test date: May, 2022	Unit is unlocked
EMC Testing	EN 50498:2010
Test date: May, 2022	
EMC Testing	EN 55032:2012
Test date: May, 2022	 VCCI-CISPR 32 – Class A
	 FCC Part 15, Subpart B – Class A
Safety Testing	62368
Test date: June, 2022	• IEC 62368
	• EN62368-1:2014 + A11:2017
	 CAN/CSA C22.2 No. 62368-1:2014
	• UL 62368-1:2014

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU