



INSTALLATION INSTRUCTIONS

Product
7160-0985

Revision
Rev.A

Form
INST-790

LEG KIT - RAM W/ CENTER SEAT 2011+

Printing Spec:PS-001

This instruction sheet covers the installation of the Gamber-Johnson leg kit into Ram trucks with center seats. Brackets on the center seat are required for installation. If your vehicle is an SSV or other model that does not have a center seat please refer to the Ram Leg Kit for SSV models, 7160-0422, and its installation instructions.

To Install:

1. If the center seat has the optional floor tray remove the tray mat and remove the tray by removing the two screws attaching it to the vehicle's floor. See FIG 1.

2. Remove the center seat from the vehicle. The seat's brackets have (2) bolts to the floor on the driver side and (2) bolts to the passenger seat frame. Disconnect the wiring to the center seat underneath the driver seat.

3. Remove the two brackets from the center seat and reinstall them into the vehicle on the driver side using the original bolts. See FIG 2, FIG 3 and FIG4.

(2) Screw Locations



FIG 1 - Front Tray Removal



FIG 2 - Center Seat Brackets

Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2017 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868

Bracket Facing Rear



FIG 3 - Front Driver Bracket

Bracket Facing Rear



FIG 4 - Rear Driver Bracket

4. Install the leg kit brackets across the reinstalled center seat brackets and the brackets attached to the passenger seat. Install the 1/4" spacers from the hardware bag between the leg kit and OEM brackets on the passenger side for leveling purposes. Bolt them in place using the 5/16-18 bolts, 5/16 washers and 5/16 nylock nuts included in the hardware bag. See FIG 5 and FIG 6.

NOTE: the leg kit brackets can be installed in either orientation to move the mounting holes to the top plate towards the front or rear. The brackets may need to be flipped to allow mounting the top plate in the extreme forward or rearward positions.

5. Install the top plate onto the leg kit using the 3/8-16 bolts and 3/8 washers included in the hardware bag. See FIG 7.



1/4" Spacer, Passenger Side

FIG 5 - Front Leg Kit Bracket



1/4" Spacer, Passenger Side

FIG 6 - Rear Leg Kit Bracket

(4) Bolts, Top Plate to Leg Kit



FIG 7 - Top Plate Installed

WARNING

- You must read and follow all of these installation instructions. Failure to follow the installation instructions may result in serious bodily injury or death
- DO NOT install or use this assembly in the area in which the airbag on the vehicle may be deployed. The installer and user of this assembly are responsible for installing and using this assembly outside the area in which an airbag may be deployed. (See Product Mounting Disclaimer Below)
- Keep these installation instructions with the product and readily available in the vehicle for future reference of other users of the product.
- Additional copies of the installation instruction can be obtained from Gamber-Johnson. If you need assistance or have any questions, go to www.gamberjohnson.com or call Gamber-Johnson at 1-800-456-6868.
- DO NOT remove the warning label from product under any circumstances.
- This assembly should not be positioned in the area where the airbag may be deployed.
- DO NOT position the equipment in front of an airbag. Equipment positioned in front of an airbag may cause serious injury or death if an airbag is activated.
- If installation of the equipment requires that the equipment be placed in front of an airbag, the airbag should be deactivated. In order to secure permission for deactivating the airbag you must contact the National Highway Traffic Safety Administration at 1-800-424-9393 to gain permission to do so. If you have any questions or need assistance, call Gamber-Johnson at 1-800-456-6868.
- High speed vehicle turns may cause parts of the assembly to swivel, interfering with the driver or other equipment.