



Testing Summary

Honeywell 10in. Tablet Docking Station

(7160-2017, 7160-2018)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational Test date: Nov., 2024	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). Unit is unlocked
Vibration – Non-Operational (Minimum Integrity) Test date: Nov., 2024	MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). Unit is unlocked
Functional Shock - Non-Operational Test date: Nov., 2024	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses 20G, 11ms half sine - Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: Nov., 2024	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses 40G, 11ms half sine - Unit is unlocked
Electrostatic Discharge – Operational Test date: Dec., 2024	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
Cycle Testing – Non-Operational Test date: Nov., 2024	30,000 cycles of the docking connector, latching and locking mechanisms

Summary of Tests Performed at Independent Facility

Test Description	Test Parameters
Humidity Test date: Nov., 2024	MIL-STD 810G, Method 507.5, Procedure II, Aggravated, Table 507.5- I Ten 24-hour cycles, temperature varied from 30°C to 60°C to 30°C at constant 95% relative humidity.
Thermal Shock Test date: Nov., 2024	85°C to -40°C, Non-Operating 2hrs at each temperature, 3 cycles

An ISO 9001:2015 certified company

Gamber-Johnson LLC · 5001 Joerns Drive · Stevens Point, Wisconsin 54481
PHONE: 1-715-344-3482 · FAX: 1-715-344-5209 · EMAIL: gamberj@gamberjohnson.com ·
www.gamberjohnson.com

Low Temperature: Operational Test date: Nov., 2024	MIL-STD 810G, Method 502.5, Procedure II -20°C Operating, 24-hour duration
Low Temperature: Storage Test date: Nov., 2024	MIL-STD 810G, Method 502.5, Procedure I -40°C Non-Operating, 24-hour duration
High Temperature: Operational Test date: Nov., 2024	MIL-STD 810G, Method 501.5, Procedure II, Table 501.5-II, Induced Conditions Five 24-hour cycles, temperature varied from 30°C to 60°C to 30°C
High Temperature: Storage Test date: Nov., 2024	MIL-STD 810G, Method 501.5, Procedure I, Table 501.5-III, Induced Conditions Seven 24-hour cycles, temperature varied from 33°C to 71°C to 33°C
EMC Testing Test date: Dec., 2024	EN 55032:2015 - CISPR 32 – Class A - FCC Part 15, Subpart B – Class A
EMC Testing Test date: Dec., 2024	EN 50498:2010
Shock – Crash Hazard Test date: Oct., 2024	SAE J1455, Section 4.11.3.5, per Figure 13 Unit is unlocked

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU

An ISO 9001:2015 certified company