



Very Well Connected™

INSTALLATION INSTRUCTIONS

Product

7160-0539

Lind Power Supply Mount Assembly

Revision

Rev.A

Form

INST-652

Printing Spec: PS-001

Installing the power supply:

1. Remove all (4) nuts from Power Supply Mount.
2. Take plate (15241) off.
3. Slide power supply under plate (15241).
4. Reattach plate (15241) back to rest of Power Supply Mount and tighten down the #8-32 nuts

Mounting the bracket to a dock:

1. Rotate the power supply mount how it is shown in Figure1 (your dock may vary), using the hardware with the supplied dock,
2. Tighten down the hardware.



Figure 1



Figure 2

Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2013 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868