

ZIRKONA DUAL ARTICULATING ARM



Rotate your device where it's needed with the Zirkona Dual Articulating Arm. Handles at each pivot point allow the user to tighten each arm in place. Smooth movement is obtained with the use of plastic sleeves in the pivot. Then, top off the mount with a joiner of your choosing and device plate needed for your device. Mounting on flat surfaces, horizontal or vertical, gives great flexibility when it's needed.

| WEIGHT | HEIGHT | WIDTH | DEPTH |
|------------------------|------------------------|---|--|
| 3.70 lbs. / 1.68 kg | 18.25 in / 46.35 cm | 17 in / 43.18 cm (fully extended) | 1.56 in / 3.96 cm (largest pole) |

Features

- · Height-adjustable pedestal 16"-24"
- Articulating arm extend 16.5" from the main pedestal
- Tension handles lock pedestal height and articulated arms in place
- · Includes hardware to attach to base
- Use with Zirkona Robust 75x75 Surface Mount base (7110-1316) or Wall Mount Base (17246) Black powder coat finish
- Use with Zirkona Robust mounts, medium or large joiners, and device plate (VESA 75/100 or AMPS) to customize the mount needed.

Construction

- · Base pedestal and inside pedestal with extended arm steel
- · Outside extended arm anodized aluminum

Placement

 Desktop or wall application for a large display, tablet, or docking station when additional adjustability is needed.



Note

- Recommend use of LOCTITE® 9460, 9461, or 9466 on all M20 size threads (See part number 7300-0510)
 - Loctite EA 9460
 - Loctite EA 9461
 - · Loctite EA 9466
- · Does NOT include joiner; joiner sold separately

Warranty

 Limited Lifetime: A limited lifetime warranty is against manufacturer defects, not normal wear and tear.

Product Selection

| PART NUMBER | DESCRIPTION |
|-------------|-------------------------------|
| 7110-1246 | Zirkona Dual Articulating Arm |