



Testing Summary

Getac F120 Tablet Docking Station

(7160-2127-00, 7160-2127-04, 7160-2127-10, 7160-2127-14)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational Test date: Feb., 2026	Getac Developmental Testing Specification per Figure 1. Test duration is two hours along three mutually orthogonal axes – not simultaneously (6 hours total). <ul style="list-style-type: none"> Unit is unlocked OEM provided operating conditions
Vibration – Operational RF Connection Test date: Feb., 2026	Getac Developmental Testing Specification per Figure 1. Test duration is two hours along three mutually orthogonal axes – not simultaneously (6 hours total). <ul style="list-style-type: none"> Unit is unlocked OEM provided operating conditions Test is performed simultaneously with operational test. Test is monitored to record any breaks in RF connectivity during vibration.
Vibration – Non-Operational (Minimum Integrity) Test date: Feb., 2026	MIL-STD-810H, Method 514.8, Category 24, per Figure 514.8E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> Unit is unlocked OEM provided operating conditions
Functional Shock - Operational Test date: Feb., 2026	MIL-STD-810H, Method 516.8, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> 20G, 11ms, terminal sawtooth Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: Dec., 2025	MIL-STD-810H, Method 516.8, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses total. <ul style="list-style-type: none"> 40G, 11ms half sine Unit is unlocked
Shock – Bump Test Test date: Feb., 2026	Getac Developmental Testing Specification Rev C. IEC 60068-2-27:2008. 1000 positive and negative pulses in the vertical axis, 2000 total. <ul style="list-style-type: none"> 25G, 6ms half sine Unit is unlocked

An ISO 9001:2015 certified company



Cycle Testing – Non-Operational Test date: Jan., 2026	<ul style="list-style-type: none"> 30,000 cycles of the docking connector, latching and locking mechanisms
Electrostatic Discharge – Operational Test date: Dec., 2025	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge

Summary of Tests Performed at Independent Facility

Test Description	Test Parameters
Humidity Test date: Dec., 2025	MIL-STD 810H, Method 507.6, Procedure II, Aggravated, Table 507.6 <ul style="list-style-type: none"> Ten 24-hour cycles, temperature varied from 30°C to 60°C to 30°C at constant 95% relative humidity.
Thermal Shock Test date: Dec., 2025	MIL-STD 810H, Method 503.7, Procedure I-C <ul style="list-style-type: none"> Three, 2-hour cycles from -40°C to 85°C to -40°C Transition time one minute
Low Temperature: Storage Test date: Dec., 2025	MIL-STD 810H, Method 502.7, Procedure I <ul style="list-style-type: none"> -40°C Non-Operating, 96-hour duration
Low Temperature: Operational Test date: Dec., 2025	MIL-STD 810H 501.7, Procedure II-Operation <ul style="list-style-type: none"> -21°C Operating, 96 hour duration
High Temperature: Operational Test date: Dec., 2025	MIL-STD 810H, Method 501.7, Procedure II <ul style="list-style-type: none"> 50°C Operating, 96-hour duration
High Temperature: Storage Test date: Dec., 2025	Getac Developmental Testing Specification <ul style="list-style-type: none"> Start Temp at 24°C, Ramp time to 85°C, 2 hours 85°C Non-Operating, 72-hour duration Ramp time to 24°C, 2 hours Hold time at 24°C, 2 hours

An ISO 9001:2015 certified company



Shock – Crash Hazard Test date: April, 2026	SAE J1455, Section 4.11.3.5, per Figure 13 <ul style="list-style-type: none"> • Unit is unlocked
EMC Testing Test date: Nov., 2025	EN 55032:2015/A11:2020 <ul style="list-style-type: none"> • CISPR 32 – Class B • FCC Part 15, Subpart B – Class B • ICES-003, Issue 7:2020 – Class B
EMC Testing Test date: Nov., 2025	EN 50498:2010

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU

An ISO 9001:2015 certified company