



Testing Summary

Zebra ET6X Tablet Docking Station

(7160-2206, 7160-2217)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational Test date: April, 2026	MIL-STD-810H, Method 514.8, Procedure 1, Category 4, per Figure 514.8C-2. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked
Vibration – Non-Operational (Minimum Integrity) Test date: April, 2026	MIL-STD-810H, Method 514.8, Category 24, per Figure 514.8E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked
Functional Shock - Non-Operational Test date: April, 2026	MIL-STD-810H, Method 516.8, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 20G, 11ms half sine • Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: April, 2026	MIL-STD-810H, Method 516.8, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 40G, 11ms half sine • Unit is unlocked
Electrostatic Discharge – Operational Test date: April, 2026	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
Cycle Testing – Non-Operational Test date: May, 2026	30,000 cycles of the docking connector, latching and locking mechanisms

Summary of Tests Performed at Independent Facility

Test Description	Test Parameters
Humidity Test date: May, 2026	MIL-STD 810H, Method 507.6, Procedure II, Aggravated, Table 507.6 <ul style="list-style-type: none"> • Ten 24-hour cycles, temperature varied from 30°C to 60°C to 30°C at constant 95% relative humidity.
Thermal Shock Test date: May, 2026	85°C to -40°C, Non-Operating <ul style="list-style-type: none"> • 2hrs at each temperature, 3 cycles

An ISO 9001:2015 certified company



Low Temperature: Operational Test date: May, 2026	MIL-STD 810H, Method 501.7, Procedure II <ul style="list-style-type: none"> -20°C Operating, 24-hour duration
Low Temperature: Storage Test date: May, 2026	MIL-STD 810H, Method 502.7, Procedure I <ul style="list-style-type: none"> -40°C Non-Operating, 72-hour duration
High Temperature: Operational Test date: May, 2026	MIL-STD 810H, Method 501.7, Procedure II, Table 501.5-II, Induced Conditions <ul style="list-style-type: none"> Five 24-hour cycles, temperature varied from 30°C to 60°C to 30°C
High Temperature: Storage Test date: May, 2026	MIL-STD 810H, Method 502.7, Procedure I, Table 501.5-III, Induced Conditions <ul style="list-style-type: none"> Seven 24-hour cycles, temperature varied from 33°C to 71°C to 33°C
EMC Testing Test date: May, 2026	EN 55032:2012 <ul style="list-style-type: none"> CISPR 32 – Class A FCC Part 15, Subpart B – Class A
EMC Testing Test date: May, 2026	EN 50498:2010
Shock – Crash Hazard Test date: May, 2026	SAE J1455, Section 4.11.3.5, per Figure 13 Unit is unlocked

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU

An ISO 9001:2015 certified company