



ZIRKONA DUAL ARTICULATING ARM

A desktop or wall mount application with swing arm adjustment for optimal use.

Rotate your device where it's needed with the Zirkona Dual Articulating Arm. Handles at each pivot point allow the user to tighten each arm in place. Smooth movement is obtained with the use of plastic sleeves in the pivot. Then, top off the mount with a joiner of your choosing and device plate needed for your device. Mounting on flat surfaces, horizontal or vertical, gives great flexibility when it's needed.



PRODUCT MEASUREMENTS

ITEM NO.	WEIGHT	HEIGHT	WIDTH	DEPTH
7110-1246	3.70 lbs. / 1.68 kg	18.25 in / 46.35 cm	17 in / 43.18 cm (fully extended)	1.56 in / 3.96 cm (largest pole)

PLACEMENT

- Desktop or wall application for a large display, tablet, or docking station when additional adjustability is needed.

CONSTRUCTION

- Base pedestal and inside pedestal with extended arm - steel
- Outside extended arm - anodized aluminum

NOTES

- Recommend use of LOCTITE® 9460, 9461, or 9466 on all M20 size threads (See part number 7300-0510)
- Loctite® EA 9460
- Loctite® EA 9461
- Loctite® EA 9466
- Does NOT include joiner; joiner sold separately

FEATURES & BENEFITS

- Height-adjustable pedestal 16"-24"
- Articulating arm extend 16.5" from the main pedestal
- Tension handles lock pedestal height and articulated arms in place
- Includes hardware to attach to base
- Use with Zirkona Robust 75x75 Surface Mount base (7110-1316) or Wall Mount Base (17246)
- Black powder coat finish
- Use with Zirkona Robust mounts, medium or large joiners, and device plate (VESA 75/100 or AMPS) to customize the mount needed.

INDUSTRIES



ENTERPRISE
& UTILITIES



MATERIAL HANDLING
& WAREHOUSING



LOGISTICS



PUBLIC SAFETY



[GAMBERJOHNSON.COM/ZIRKONA](https://www.gamberjohnson.com/zirkona)
+1 (800) 756-9198
SALES@GAMBERJOHNSON.COM



MOUNT IT. POWER IT. CARRY IT.